

Product sheet 2016

Topstyle COMPACT

1-strip engineered boards in European Oak:



**picture: an example for Topstyle COMPACT
with following surface:**

colour: European Oak, oxidative oiled
treatment: brushed surface
remark: "Nature Select"; Natural grading of European Oak with
sound knots and variations in the texture of wood

Product sheet 2016

Topstyle COMPACT

Characteristic:

Standardised boards in fixed width of 180 mm.

Assortment:

Beside of the grading SELECT EXCLUSIVE with free of knots appearance, we offer also a natural assortment, called NATURE SELECT, with some healthy knots and natural variation in the colour of wood.

Dimension:

16/4 x 180 x falling lengths from 1.800 – 2.400 [mm]

construction: 4 mm toplayer above 12 mm birch-plywood; as an option we are able to produce also in 3-layer construction

Surface:

- **Colour:** All existing colours from range of the Topstyle-range
- **Treatment:** Standard in brushed surface
Option: following surface treatment can be done in addition:
 - sanded
 - Hand-scraped
 - „Sawnmark“
 - „Relief“ (= heavily brushed surface)

Profile and further information:

- Tongue& groove on 4-sides with microbevel on longside
- FSC (as an option)- no.: TT-COC-005277
- Certification according to German emission law: Z-156.607-1362; 3-schichtige Version mit Z-156.607-1362; it means that our product are proved and controlled in keeping a safety limit vs. toxical emissions and VOC
- Fire resistance category according to EN 13501: Dfl-S1
- Thermal resistance R: 0,11 [m² x K/ W]