

Product sheet 2016

Topstyle Fishbone/ Herring

Oak-floor in traditional pattern of fishbone:



Picture: an example for Topstyle Fishbone/ Herring with following surface:

colour: Oslo/ no.14
treatment: sanded surface
remark: AB-grading, i.e. few small sound knots allowed

Product sheet 2016

Topstyle Fishbone/ Herring

Characteristic:

Classic and elegant type of wooden floor used since time immemorial in wealthy and spacy city houses. By altering the perspective the gloss from the left to the right elements prelude a mystic change in gloss.

Assortment:

As the standard, we are using a **grading AB**, which means that few small sound knots allowed at a harmonious piece in oak.

On request, we even can offer **quarter& rift** cut elements in order to provoke a distinct orientation of the single element. That special grading adapt to puristic style of modern houses.

Dimension:

16/4 x 100 x 600 [mm]

As an option, we can manufacture dimensions on special request. The proportion in length to width of 6:1 has stand the test. However, also other proportions can generate effective impressions as well.

Construction: 4mm toplayer above 12 mm birch-plywood.

Surface:

- **Colour:** All existing colours from the Topstyle range
- **Treatment:** standard in brushed surface
Option: sanded surface

Profile & further information:

- tongue& groove on 4-side; microbevel all around
- Certification according to German emission law: Z-156.607-1362
- FSC (option): TT-COC-005277
- Fire resistance category according to EN 13.501: Dfl-S1
- Thermal resistance R: 0,11 [m² x K/ W]